



# 6019

## A6 Quick Dri

### Siliconized Acrylic Sealant

- Paintable in 30 Minutes
- Exceeds ASTM C-834 (TYPE OP, Grade -18C)
- Interior/Exterior
- Flexible
- Water Tight Seal
- Cured caulk is mold & mildew resistant

Gardner A6 Quick Dry is a high quality Siliconized Acrylic multi-purpose caulk, designed to form a flexible water tight seal while delivering strong adhesion to a variety of substrates both interior & exterior. With its quick drying capability, A6 can be painted in 30 minutes providing maximum efficiency to the end user.

Gardner A6 Fast Dry can be used on wood, metal, brick, concrete, plaster, masonry, drywall, glass or tile. It is ideal for sealing seems around doors, windows, woodwork, baseboards, and many other household surfaces.

Clean all surfaces of dirt, dust, old caulk, loose paint, wax, grease oil, mold & mildew and any other foreign substances. Ensure the surfaces are clean and dry.

#### DIRECTIONS

Trim nozzle to the desired bead size and load in caulk gun. While applying sealant, hold nozzle at a 45° angle, pushing sealant into the gap. Sealant may be smoothed with a wet finger or damp sponge or brush. Important: When smoothing sealant, the remaining bead must be no smaller than 1/8" or larger than 1/2". When sealing larger cracks, a backing material must be used. Each 10 fl. oz. cartridge covers approximately 55 linear feet per 3/16" bead. Excess sealant can be cleaned up before it dries with a wet cloth. This sealant can be painted in 30 minutes, depending upon bead size and weather conditions.

- For best paint results during high humidity and/or cool weather, extended curing time may be required
- Do not caulk if rain or freezing conditions are anticipated within 24 hours of exterior application
- Not intended for marine use, surfaces submerged in water, or repair of surface defects
- **KEEP FROM FREEZING**

#### CLEAN UP

Excess sealant can be cleaned up before it dries with a wet cloth. Use soap and water to clean hands and tools.

PRODUCT INFORMATION	
Product Code	6019-1-61
Unit Size	10 fl. Oz tube
Unit Weight	1.1 lbs
Color	White
Pack	12 tubes / case
UPC	758706601952
PHYSICAL & PERFORMANCE CHARACTERISTICS	
ASTM Specs	C834 (Type OP, Grade -18C)
Vehicle	Modified Acrylic
Polymer	Acrylic
VOC (less water & exempt)	22.0 g/l
VOC (by wt.)	1.25%
Weight Solids %	84.1%
Volume Solids	72.4%
Paintable	Yes
Working/Tooling Time	5-10 minutes
Tack Free	30 minutes
Full Dry	24 hours
Paint Time	30 Minutes
Full Cure	48 hours
Coverage	55 linear feet per 3/16" bead
Mildew Resistance	Yes
Shelf Life	12 months
Wt./Gal	14.38 lbs.
Wt./Tube	1.20 lbs.
Viscosity	20-25 g/sec.
Elongation-at-Break	150%
Tensile Maximum	190 psi.
Freeze/Thaw Stability	3 cycles
Flash Point	245 F